

Beta Analytic, Inc. 4985 SW 74th Court Miami, FL 33155 USA

Tel: 305-667-5167 Fax: 305-663-0964

info@betalabservices.com

ISO/IEC 17025:2017-Accredited Testing Laboratory

Summary of Results - % Biobased Carbon Content ASTM D6866-21 Method B (AMS) Certificate Number:

Validation:

Submitter

Tyler Trimbath

Company

Bio Rejuv, LLC.

Date Reported

April 23, 2021

Submitter Label

Roof Rejuv / USDA Application

RESULT:

90 % Biobased Carbon Content (as a fraction

of total organic carbon)

Laboratory Number

Percent modern carbon (pMC)

90.26 +/- 0.28 pMC

Atmospheric adjustment factor (REF)

100.0; = pMC/1.000

Disclosures: All work was done at Beta Analytic in its own chemistry lab and AMSs. No subcontractors were used. Beta's chemistry laboratory and AMS do not react or measure artificial C 14 used in biomedical and environmental AMS studies. Beta is a C14 tracer-free facility. Validating quality assurance is verified with a Quality Assurance report posted separately to the web library containing the PDF downloadable copy of this report.

Precision on the RESULT is cited as +/- 3% (absolute). The cited precision on the analytical measure (pMC) is 1 sigma (1 relative standard deviation). The reported result only applies to the analyzed material. The accuracy of the RESULT relies on the measured carbon in the analyzed material having been in recent equilibrium with CO2 in the air and/or from fossil carbon (from living more than 40,000 years ago such as petroleum or coal. The RESULT only applies to relative carbon content, not to relative mass content. The RESULT is calculated by adjusting pMC by the applicable "Atmospheric adjustment factor (REF)" cited in this report.



Beta Analytic, Inc.

4985 SW 74th Court Miami, FL 33155 USA Tel: 305-667-5167

Fax: 305-663-0964 info@betalabservices.com

ISO/IEC 17025:2017-Accredited Testing Laboratory

Summary of Results - % Biobased Carbon Content ASTM D6866-21 Method B (AMS) Certificate Number:

Validation:

75 6

Submitter Tyler Trimbath

Company Bio Rejuv, LLC.

Date Reported April 23, 2021

Submitter Label Roof Rejuv / USDA Application


RESULT: 90 % Biobased Carbon Content (as a fraction

of total organic carbon)

Laboratory Number

Percent modern carbon (pMC) 90.26 +/- 0.28 pMC

Atmospheric adjustment factor (REF) 100.0; = pMC/1.000





Beta Analytic, Inc. 4985 SW 74th Court

Miami, FL 33155 USA Tel: 305-667-5167 Fax: 305-663-0964

info@betalabservices.com

ISO/IEC 17025:2017-Accredited Testing Laboratory

% Biobased Carbon Content ASTM D6866-21 Method B (AMS)

Explanation of Results

The result was obtained using the radiocarbon isotope (also known as Carbon-14, C14 or 14C), a naturally occurring isotope of carbon that is radioactive and decays in such a way that there is none left after about 45,000 years following the death of a plant or animal. Its most common use is radiocarbon dating by archaeologists. An industrial application was also developed to determine if consumer products and CO2 emissions were sourced from plants/biomass or from materials such as petroleum or coal (fossil-based). By 2003 there was growing demand for a standardized methodology for applying Carbon-14 testing within the regulatory environment. The first of these standards was ASTM D6866-04, which was written with the assistance of Beta Analytic. Since ASTM was largely viewed as a US standard, European stakeholders soon began demanding an equivalent CEN standard while global stakeholders called for ISO standardization.

The analytical procedures for measuring radiocarbon content using the different standards are identical. The only difference is the reporting format. Results are usually reported using the standardized terminology "% biobased carbon". Only ASTM D6866 uses the term "% biogenic carbon" when the result represents all carbon present (Total Carbon) rather than just the organic carbon (Total Organic Carbon). The terms "% biobased carbon" and "% biogenic carbon" are now the standard units in regulatory and industrial applications, replacing obscure units of measure historically reported by radiocarbon dating laboratories e.g. disintegrations per minute per gram (dpm/g) or radiocarbon age.

The result was obtained by measuring the ratio of radiocarbon in the material relative to a National Institute of Standards and Technology (NIST) modern reference standard (SRM 4990C). This ratio was calculated as a percentage and is reported as percent modern carbon (pMC). The value obtained relative to the NIST standard is normalized to the year 1950 AD so an adjustment was required to calculate a carbon source value relative to today. This factor is listed on the report sheet as the terminology "REF".

Interpretation and application of the results is straightforward. A value of 100% biobased or biogenic carbon would indicate that 100% of the carbon came from plants or animal by-products (biomass) living in the natural environment and a value of 0% would mean that all of the carbon was derived from petrochemicals, coal and other fossil sources. A value between 0-100% would indicate a mixture. The higher the value, the greater the proportion of naturally sourced components in the material.

Quality Assurance Report

This report provides the results of reference materials used to validate radiocarbon analyses prior to reporting. Known-value reference materials were analyzed quasi-simultaneously with the unknowns. Results are reported as expected values vs measured values. Reported values are calculated relative to NISTSRM-1990C and corrected for isotopic fractionation. Results are reported using the direct analytical measure percent modern carbon (pMC) with one relative standard deviation. Agreement between expected and measured values is taken as being within 2 sigma agreement (error x 2) to account for total laboratory error.

QA MEASUREMENTS

Reference 1

Expected Value: 96.69 +/- 0.50 pMC

Measured Value: 96.36 +/- 0.30 pMC

Agreement: Accepted

....

Reference 2

Expected Value: 129.41 +/- 0.06 pMC

Measured Value: 129.45 +/- 0.39 pMC

Agreement: Accepted

Reference 3

Expected Value: 0.44 +/- 0.10 pMC

Measured Value: 0.46 +/- 0.03 pMC

Agreement: Accepted

COMMENT: All measurements passed acceptance tests.

Validation: